

# supermax

## TECHNICAL HIGHLIGHTS



Model: Compact  
 Main CPU's: 1  
 Max number of workstations supported: 32  
 Disk capacity:  
 85-760 MB, 170 MB typical  
 Expansion slots: 1



Model: Slimline  
 Main CPU's: 1  
 Max number of workstations supported: 64  
 Disk capacity:  
 85 MB - 5 GB, 380 MB typical  
 Expansion slots: 3



Model: Vertical  
 Main CPU's: 1-8  
 Max number of workstations supported: 512 (soon 1024)  
 Disk capacity:  
 85 MB up to more than 30 GB, 760 MB typical  
 Expansion slots: 9 + 12



Model: Rack  
 Main CPU's: 1-8  
 Max number of workstations supported: 512 (soon 1024)  
 Disk capacity:  
 85 MB up to more than 30 GB, 760 MB typical  
 Expansion slots: 9 + 12

# supermax

## ■ CENTRAL PROCESSING UNITS:

Up to 8 main CPUs supporting user-mode applications:

### MC68020 CPU:

Based on 20 MHz Motorola 68020 processor with 16 KB of instruction and data caches and MC68881 IEEE floating point unit (16 MHz).

### MC68030 CPU:

Based on 25 MHz or 33 MHz Motorola 68030 processor with 128 KB of instruction and data caches and MC68882 IEEE floating point unit (20 MHz or 25 MHz).

### R3000 CPU:

Based on 20 MHz or 25 MHz MIPS R3000 processor with 128 KB of instruction and data caches and R3010 IEEE floating point unit.

Supermax® Vertical and Rack systems may use processors of the same type or a combination of MC68030 and R3000.

## ■ MEMORY OPTIONS:

Maximum total memory per CPU is 256 MB in increments of 1 MB and 4 MB. Memory expansion modules have 1-4 increments (1-16 MB) with error correcting code (ECC).

## ■ INTELLIGENT I/O CONTROLLERS:

Up to 16 intelligent units supported including up to 8 main CPUs.

### DIOC (Disk I/O Controller).

Supports 4 serial ports, streaming tape unit, floppy drive, 1/2" tape drive, optical disks and up to 6 SCSI Winchester disks.

### DIOC III (High Performance Disk I/O Controller).

Supports streaming tape unit and floppy drive. Provides 2 SCSI buses for connection of up to 2\*7 Winchester disk drives. Supports disk mirroring and disk striping.

### SIOC (Serial I/O Controller).

Supports 8-63 serial, asynchronous devices: terminals, printers and modems. In addition a parallel Centronics printerport is provided.

### CIOC (Communications I/O Controller).

Supports 2 independent synchronous communication ports for BSC, SDLC, HDLC protocols at speeds up to 64 kbps. V.24/RS232C, V.11/RS422 and X.21 interfaces are provided.

### NIOC (Network I/O Controller).

Supports 32 or 64 logical ports for terminal, printer and PC devices connected through Supermax LAN (Ethernet®, IEEE 802.3). Supports TCP/IP and ScaNet®.

## ■ DISK OPTIONS:

85, 170, 380 and 760 MB Winchester disks.  
1 GB optical disk.

## ■ TAPE BACK-UP:

60 and 150 MB streaming tape.  
2 GB 8 mm video streaming tape  
1600/3200 bpi and 1600/6250 bpi  
1/2" tape stations.

## ■ UPS:

1000 VA and 2000 VA No-break systems.

## ■ DISKETTE STATION:

5 1/4" floppy drive supporting DDE format (560 KB) or MS-DOS® format (360 KB and 720 KB).

## ■ TERMINALS, PRINTERS AND PCs:

Supermax supports a wide range of terminals, printers and workstations. DDE supplies devices supporting ISO/DIS 8859 character set. VT100/VT200® and IBM PC/PS® compatible devices are recommended.

## ■ OPERATING SYSTEM:

The Supermax system is based on UNIX® System V. The operating System conforms to AT&T's System V Interface Definition (SVID) and has passed AT&T's System V Verification Suite (SVVS). The System has been enhanced with dynamic load balancing, virtual terminal interface and supports the international 8-bit ISO/DIS 8859 character set.

Supermax is a trademark of Dansk Data Elektronik A/S.

UNIX is a trademark of AT&T.

Ethernet is a trademark of Xerox Corporation.

ScaNet is a trademark of DATACO.

VT100/VT200 is a trademark of Digital Equipment Corp.

IBM PC/PS is a trademark of International Business Machines.

MS-DOS is a trademark of Microsoft Corp.