



RC 3665
75 cps
Paper Tape Punch

- 5, 7, AND 8 CHANNEL ISO STANDARD TAPE
- EASY TO HANDLE, EASY TO LOAD
- AUTOMATIC TAPE CHECKS
- AUTOMATIC TAKE-UP SPOOL
- COMPACT DESIGN



GENERAL

The RC 3665 is capable of punching 5, 7, and 8-channel Paper Tape in accordance with appropriate sections of ISO standard R 1154 at an asynchronous speed of 75 characters per second.

SPECIFICATIONS

Punching speed:	75 characters per second, asynchronous
Supply spool capacity:	Approximately 300 m (1000 feet) of tape, corresponding to about 120,000 characters
Tape widths:	
8 channel ISO	25.4 mm (1")
7 channel ISO	22.2 mm ($7/8$ ")
5 channel ISO	17.5 mm ($11/16$ ")
Tape media:	Paper, oiled or non-oiled, plastic, mylar, or metalized mylar.
Tape roll sizes:	
Outer	200 mm ($73/4$ ") maximum
Inner	50 mm (2") minimum
Tape feed system:	Incremental Single capstan drive, independent of sprocket holes
Tape punching system:	9 solenoid operated punching pins
Standard features:	Tape break detector Tape low indicator Removable transparent cover and chad box
Special remark:	Punched output tape can either run free or be fed back to a take-up spool inside the unit
Heat dissipation:	720 kJ/h (172 kcal/h, 683 BTU/h)
Power requirement:	220 V AC 200 W
Mounting:	Desk top

DIMENSIONS

Height:	19.8 cm ($73/4$ ")
Width:	22.0 cm ($85/8$ ")
Depth:	43.2 cm ($167/8$ ")
Weight:	13 kg ($283/4$ lbs)

RCSL 42-i 0391

This datasheet is of a summary nature and specifications are subject to change without prior notice.