
RCSL No: 31-D542

Edition: January 1979

Author: Palle Andersson

Title:

RC8000 CASSETTE TAPE PROCESS

Keywords:

RC8000, external process.

Abstract:

This paper describes the conventions of an external process controlling a cassette tape unit connected to RC8000.

(14 printed pages)

Copyright © 1982, A/S Regnecentralen af 1979

RC Computer A/S

Printed by A/S Regnecentralen af 1979, Copenhagen

Users of this manual are cautioned that the specifications contained herein are subject to change by RC at any time without prior notice. RC is not responsible for typographical or arithmetic errors which may appear in this manual and shall not be responsible for any damages caused by reliance on any of the materials presented.

General Rules.

Operations can be initiated by an internal process that has initialized or reserved the device.

The device is sensed before each operation. If the status word indicates an intervention by the operator in the local mode, the name of the process is removed (together with the present reservation) and all messages are answered with the result: receiver does not exist. The device is now in the state: document removed.

When the operator switches back to remote mode, the device state will be set to: unidentified document mounted.

When the device is named by the monitor procedure create peripheral process, the device state becomes: identified document mounted.

File and Block Count.

All answers from magnetic tape contain a file and block number defining the position of the tape after the operation. These numbers are undefined after mounting. File and block number are reset to zero only when load point is sensed after an operation.

The file number is increased by one after the output of a tape mark or the sensing of a tape mark during a forward operation. It is decreased by one when a tape mark is sensed after a backward operation. The block number is increased by one when a block is input, output, or upspaced. If a tape mark is sensed during a forward operation, the block number is

set to zero.

The block number is decreased by one when a block is backspaced.

These simple file and block numbers are based solely on a count of initiated operations and sensed status bits. There is no check against file and block numbers recorded in labels and data blocks.

Density.

The density of the station is NRZ (800 bpi).

Block Size.

The storage area defined by input or output operations must not exceed 2080 halfwords. A violation will be treated as an unintelligible message.

Sense Operation.

The device is sensed and the status word delivered as an answer.

Input Operation.

A block of characters is input to a storage area within the sending process. Each storage word contains three 8-bit characters. Unused character positions in the last input word are filled with NUL characters.

Input is terminated, when

- 1) data have been transferred to the last storage address, or
- 2) the block on the tape is exhausted, or
- 3) data overrun is detected, or
- 4) timer error is detected,

whichever occurs first.

Output Operation.

A storage area within the sending process is output as one block. Each storage word is output as three 8-bit characters.

Output is terminated, when

- 1) the whole block has been output, or
- 2) output of an all-zero even parity character by NRZ is attempted, or
- 3) data overrun is detected,

whichever occurs first.

Erase Operation.

Erases a length of tape.

Move Operation.

Moves the tape in accordance with the move operation defined in the message (if the move operation is negative or greater than six it is treated as a sense operation):

move operation:	0	upspace file
	1	upspace block
	2	backspace file
	3	backspace block
	4	rewind tape
	5	unload tape
	6	position tape

Move operation 6 positions the tape as specified in the message. If the specified file or block number is negative the operation is treated as a sense operation. If the block specified does not exist the tape will be positioned at the start of the file after the one specified.

Move operation 5 rewinds the tape and when BOT is sensed sets the unit off-line.

If the specified file and block number is zero, a rewind operation is always executed.

Output Tape Mark.

Outputs two tape marks and positions after the first.

Set Mode Operation.

This operation is dummy except at load point when a check of the actual density is performed.

Mode.

Characters can be input or output in several ways defined by the sum of

numbers specifying parity, density, and trail.

mode = slew < 8 + ecma < 7 + trail < 4 + density < 2 + parity

parity: 0 odd parity

density: 1 800 bpi/nrz

trail: the number of characters not to be transferred from the last doubleword of the storage area specified in an output operation. Allowed numbers 0, 1, 2, 3, 4, 5. Only relevant for output operations. If number > 5 the trail will be set to 5.

ecma: 0 reads and writes the tape according to ECMA-34 Standard 2nd Edition (July 1973)

1 read only. Tape is written according to ECMA-34 Standard 1st Edition (September 1971)

slew: 0 normal

1 slew mode

Status Bits.

0 intervention

1 parity error (after input, output, and erase)

2 timer (after input and output)

3 data overrun (after input and output)

4 block length error (after input)

- 5 EOT sensed (after input, output, erase, and upspace)
- 6 BOT sensed (after rewind and backspace)
- 7 tape mark sensed (after input, output tape mark, upspace, and backspace)
- 8 write-enable sensed (permanent)
- 9 mode error

Special Status Actions.

Timer.

If a timer error is detected in the status word the unit will be rewound the file no and block no will be set to zero.

Write Enable.

If the operation is output, erase, or output tape mark and the status word does not indicate write-enable, the operation will be treated as a sense operation.

Mode Error.

Mode error will only occur when the commands input/output, or set mode are used. If a mode error is detected in the status word a possible input or output operation is not executed. File no and block no are unchanged. The command which causes the mode error will be treated as a sense operation.

Messages and Answers.

operation:	message:	answer:
sense	0	status word 0 0 file number block number
input	$3 < 12 + \text{mode}$ first storage address last storage address	status word number of halfwords number of characters file number block number
output	$5 < 12 + \text{mode}$ first storage address last storage address	status word number of halfwords number of characters file number block number
erase	$6 < 12 + 0$	status word 0 0 file number block number
move	$8 < 12 + 0$ move operation file number block number	status word 0 0 file number block number

operation:	message:	answer:
output tape mark	$10 < 12 + 0$	status word 0 0 file number block number
set mode	$14 < 12 + \text{mode}$	status word 0 0 file number block number

RETURN LETTER

Title: RC8000 CASSETTE TAPE PROCESS

RCSL No.: 31-D542

A/S Regnecentralen af 1979/RC Computer A/S maintains a continual effort to improve the quality and usefulness of its publications. To do this effectively we need user feedback, your critical evaluation of this manual.

Please comment on this manual's completeness, accuracy, organization, usability, and readability:

Do you find errors in this manual? If so, specify by page.

How can this manual be improved?

Other comments?

Name: _____ Title: _____

Company: _____

Address: _____

Date: _____

Thank you

..... Fold here

..... Do not tear - Fold here and staple

Affix
postage
here

 **REGNECENTRALEN**
af 1979

Information Department
Lautrupbjerg 1
DK-2750 Ballerup
Denmark